



NOTES:

1. SEDIMENT CONTROL LOGS ARE TO BE USED ON EXISTING CURB INLETS WHICH ARE LOCATED ADJACENT TO OCCUPIED TRAVEL LANES WITHIN THE DISTURBED LIMITS OF A PROJECT AS SHOWN ON THE PLANS.
2. SEDIMENT CONTROL LOGS ARE TO BE INSTALLED AND MAINTAINED PER THE MANUFACTURER'S INSTRUCTIONS AND PROPERLY WEIGHTED IN ORDER TO REMAIN SECURELY IN PLACE. INSTALLATION MUST MEET THE CONSTRUCTION INSPECTOR'S APPROVAL.
3. SEDIMENT CONTROL LOGS ARE TO BE CONSTRUCTED OF WOOD FIBERS, SYNTHETIC FIBERS OR OTHER SUITABLE MATERIAL SUFFICIENT TO RETAIN ITS SHAPE AND ENCASED IN A UV STABILIZED FILTERING MEDIA OF SUFFICIENT STRENGTH TO RETAIN SEDIMENT.
4. SEDIMENT CONTROL LOGS ARE TO BE APPROVED BY THE ENGINEER PRIOR TO INSTALLATION.
5. SEDIMENT CONTROL LOGS ARE TO BE USED ONLY ON COG 402/403 STANDARD CURB INLETS; THEY ARE NOT AN ADQUATE SEDIMENT CONTROL DEVICE FOR NCDOT 840.01 CATCH BASINS.

C I T Y O F G R E E N S B O R O

SEDIMENT CONTROL LOG INSTALLATION FOR EXISTING CURB INLETS NEXT TO TRAFFIC

STD. NO.

450

REV.

03/09